



## Search Results -

| Terms               | Documents |  |
|---------------------|-----------|--|
| 16 and optical axis | 18        |  |

US Patents Full-Text Database
US Pre-Grant Publication Full-Text Database
JPO Abstracts Database
EPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Database:

|                | 16 and | d optical | axis  |   | 1 |       |
|----------------|--------|-----------|-------|---|---|-------|
| Refine Search: |        |           | ····· | ▼ | 1 | Clear |

## Search History

Today's Date: 4/13/2001

| <b>DB Name</b>                | <u>Query</u>                | Hit Count | Set Name  |
|-------------------------------|-----------------------------|-----------|-----------|
| USPT,PGPB,JPAB,EPAB,DWPI,TDBD | 16 and optical axis         | 18        | <u>L7</u> |
| USPT,PGPB,JPAB,EPAB,DWPI,TDBD | 15 and edges                | 46        | <u>L6</u> |
| USPT,PGPB,JPAB,EPAB,DWPI,TDBD | 13 and compensation         | 72        | <u>L5</u> |
| USPT,PGPB,JPAB,EPAB,DWPI,TDBD | 13 and achieve compensation | 1         | <u>L4</u> |
| USPT,PGPB,JPAB,EPAB,DWPI,TDBD | 12 and distortion           | 241       | <u>L3</u> |
| USPT,PGPB,JPAB,EPAB,DWPI,TDBD | 11 and photosensors         | 1749      | <u>L2</u> |
| USPT,PGPB,JPAB,EPAB,DWPI,TDBD | sensor and optics           | 32474     | <u>L1</u> |